

C SERIES – LIGHT COMMERCIAL



C 21 Heat and Chill Heat Pump Specifications

| Performance Condition: Air 27°C / Water 26°C | | |
|--|------------|-------------------|
| Heating Capacity | kW | 26.1 |
| Running Current | A | 17.5 |
| Performance Condition: Air 19°C / Water 26°C | | |
| Heating Capacity | kW | 21.0 |
| Running Current | A | 17.5 |
| Heating Power Input | kW | 3.8 |
| Cooling Capacity | kW | 13 |
| Cooling Power Input | kW | 4.8 |
| Running Current | A | 17.5 |
| Power Supply | V/Ph/Hz | 240/1/50 |
| Compressor Quantity | 1 | 1 |
| Compressor | | Scroll |
| Fan Quantity | | 1 |
| Fan Power Input | W | 150 |
| Fan Rotate Speed | RPM | 850 |
| Fan Direction | | Horizontal |
| Noise | dB(A) | 56 |
| Water Connection | Mm | 40 |
| Water Flow Volume | l/m | 116 |
| Water Pressure Drop (max) | kPa | 12 |
| Unit Shipping Dimensions | Mm (L/W/H) | 1200 x 490 x 1410 |
| Net Weight / Shipping Weight | kg | 108 / 123 |

Cooling capacity is based on 19 °C ambient air temperature and 26°C water temperature

