

C SERIES – LIGHT COMMERCIAL



C 10 Heat and Chill Heat Pump Specifications

| Performance Condition: Air 27°C / Water 26°C | | |
|--|------------|-----------------|
| Heating Capacity | kW | 13 |
| Running Current | A | 8.7 |
| Performance Condition: Air 19°C / Water 26°C | | |
| Heating Capacity | kW | 10 |
| Running Current | A | 8.7 |
| Heating Power Input | kW | 1.9 |
| Cooling Capacity | kW | 5.4 |
| Cooling Power Input | kW | 2.2 |
| Running Current | A | 8.7 |
| Power Supply | V/Ph/Hz | 240/1/50 |
| Compressor Quantity | 1 | 1 |
| Compressor | | Rotary |
| Fan Quantity | | 1 |
| Fan Power Input | W | 120 |
| Fan Rotate Speed | RPM | 850 |
| Fan Direction | | Horizontal |
| Noise | dB(A) | 54 |
| Water Connection | Mm | 40 |
| Water Flow Volume | l/m | 75 |
| Water Pressure Drop (max) | kPa | 3.5 |
| Unit Shipping Dimensions | Mm (L/W/H) | 970 x 405 x 615 |
| Net Weight / Shipping Weight | kg | 55 / 65 |

Cooling capacity is based on 19 °C ambient air temperature and 26°C water temperature

