

C Series – Semi Commercial

Heat Pump Specifications

C Series Specifications - Semi Commercial Operation - Heating & Cooling, with auto defrost

Model		Oasis C38T	Oasis C47T	Oasis C58T
Performance Condition: Air 27°C / Water 26°C				
Heating Capacity	kW	49	60	76
Running Current	A	11.5	16.6	23
Performance Condition: Air 19°C / Water 26°C				
Heating Capacity	kW	38	47	58
Heating Power Input	kW	7	8.7	12.8
Cooling Capacity	kW	24	33.5	45
Cooling Power Input	kW	7.8	10.5	12.7
Running Current	A	11.5	16.6	23
Power Supply	V/Ph/Hz	400V/3/50	400V/3/50	400V/3/50
Compressor Quantity		2	2	2
Compressor		Scroll	Scroll	Scroll
Fan Quantity		2	2	2
Fan Power Input	W	120x2	120x2	120x2
Fan Rotate Speed	RPM	830	830	830
Fan Direction		Horizontal	Horizontal	Horizontal
Noise	dB(A)	61	61	61
Water Connection	Mm	50	50	50
Water Flow Volume	l/m	200	250	333
Water Pressure Drop (max)	kPa	25	25	25
Unit Shipping Dimensions (L/W/H)	Mm	1520 X 790 X 1360	1520 X 790 X 1360	1520 X 790 X 1360
Net / Shipping Weight	kg	252/286	254/295	257/297

Cooling capacity is based on 19 °C ambient air temperature and 26°C water temperature

Oasis C38T / Oasis C47T / Oasis C58T Dimensions

