



# SERIES X24 | X285 | X28T

- World class sophisticated yet easy to use Oasis LCD controller
- Hydrophilic fin coil coating ABS cabinets
- Titanium coil (20 year warranty)
- Fan design (whisper quiet)
- Reverse cycle defrost
- Internal flow switches
- Built-in drains
- Slimline design
- Ozone friendly and highly efficient
- R410a refrigerant









### FIXED SPEED X SERIES

### X24 | X28S | X28T

## The X Series is the top of the line fixed speed range of heat pumps offered by Sunlover and Oasis.

This top of the range unit has an automatic reverse cycle defrost system which allows the unit to operate in temperatures below 0°c.

At approximately 10° c, all heat pumps will start to ice up. If the unit is not fitted with a reverse cycle function it will stop operating.

At low ambient air temperatures the Oasis X Series will inject hot refrigerant through the coils allowing the ice to melt and the unit will keep operating.

We use ozone friendly and highly efficient R410A refrigerant to ensure optimum performance. Our units are fitted with a world class digital controller to drive the entire system and are reliable and of the highest quality. The C series units are able to water sample and also have a time clock function to make sure running costs are kept to a minimum.

#### **Key Features**

- ✓ Latest in Heat Pump technology
- Environmentally friendly refrigerant
- Supplying heat pumps into the Australian and New Zealand market for over 20 years
- Grade one titanium heat exchangers
- ✓ All X Series units have electronic thermostatic expansion valves
- ✓ Flow switches in all units
- 20 year warranty on Titanium Heat exchanger against corrosion
- Digitally controlled thermostat
- Oasis LCD Controller with water sampling and time clock control

- Whisper quiet fans
- Reverse cycle defrost standard for low ambient operation
- ✓ 100% factory tested
- Energy Efficient
- ✓ Nationwide back up
- Scroll and rotary compressor
- Exported to Europe and Asia
- Hydrophilic Coil protection on all models

Model		Oasis X24	Oasis X28	Oasis X28 T		
Performance Condition: Air 27°C / Water 26°C						
Heating Capacity	kW	26.1	28.8	28.8		
Running Current	Α	17.5	21.3	8.7		
Performance Condition: Air 19°C / Water 26°C						
Heating Canacity	L\\/	21	25	25		

C Series Specifications – Heating and Cooling, with auto defrost

-						
Performance Condition: Air 19°C / Water 26°C						
Heating Capacity	kW	21	25	25		
Running Current	Α	17.5	21.3	8.7		
Heating Power Input	kW	3.8	4.3	4.3		
Power Supply	V/Ph/Hz	240/1/50	240/1/50	400/3/50		
Noise	dB(A)	56	56	56		
Water Connection	mm	40	40	40		
Water Flow Volume	l/m	116	150	150		
·						

